

AquaMatic® Fluid Ejectors

Aquamatic Fluid Ejectors are designed for commercial applications and are constructed with chemical resistant PVC so your softening brine or deionization regenerants can be safely drawn into the systems.



Aquamatic offers both NPT and Socket weld styles from ½" to 2" to match a range of installations. Each size has multiple colors that specify which orifice size the Ejector is built with. To properly select the correct unit, the supply pressure and solution to be drawn must be known. Referencing the charts for the draw factor and solution specific gravity will allow you to match the right Ejector to the required regeneration flow rate for the media.

When paired with an Aquamatic Easy Nest valve kit and Stager assembly, Aquamatic Ejectors provide a complete solution for systems requiring low pressure drop and a superior service life.

Specifications

- Min Operating Pressure 20 psi (1.37)
- Max Operating Pressure 125 psi (8.6 bars)
- Operating Temperature up to 140°F (60°)
- Body Material PVC

*For optimum performance, ejectors should be installed with a section of straight pipe extending from the discharge side.

16605 West Victor Rd. New Berlin, WI 53151 | P: 262-326-0100 | www.aq-matic.com | techsupport@aq-matic.com

© 2016 AQ Matic Valve and Controls Company, Inc. All rights reserved.

All AQ Matic trademarks and logos are owned by AQ Matic or its affiliates. All other registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, AQ Matic reserves the right to change specifications without prior notice. AQ Matic is an equal opportunity employer.



PT Watermart Perkasa
Email: sales@water.co.id Phone: +62-21-316-1671
Whatsapp (text only): +62815-8609-3500
Website: www.water.co.id