

Runxin F73 (17603)

Overview

Runxin F73 is a meter-type automatic valve control with twin alternating softener configuration, designed to provide continuous soft water supply through a two-tank system (U1 and U2). With a flow capacity of up to 3.5 m³/h, this product is suitable for households, light commercial, and small industries with smart and energy efficient regeneration needs. The system is capable of running service, backwash, brine & slow rinse, brine refill, and fast rinse processes automatically or manually.



Specifications:

- Model: F73 (17603)
- Jenis Kontrol: Meter Type
- Konfigurasi: Twin Alternating Softener (2 tangki, 1 valve)
- Inlet / Outlet 1" M
- Drain 1/2" M
- Brine Line Connector 3/8" M
- Mounting Base 2-1/2"-8NPSM
- Riser Pipe 1.05" OD
- Flow Rate Maksimal 3.5 m³/h
- Ukuran Filter Tank 8"-14"
- Tekanan Air Operasi: 0.15 – 0.6 MPa
- Temperatur Air: 5 – 50°C
- Tingkat Kekeruhan Air: < 5 FTU
- Temperatur Lingkungan: 5 – 50°C
- Kelembaban Relatif: ≤ 95% (pada 25°C)
- Adaptor Daya: AC100240V / 5060Hz → DC12V/1.5A

Material :

- Ceramic material
- Engineering plastic
- Internal Seal/Gasket: Chemical resistant rubber
- Riser Pipe: Plastic/SS with 1.05" OD
- Power Adapter: Standard AC/DC temperature and humidity resistant electronic components

Applications:

- Small Industries
- Commercial Laundry
- RO System & Small Scale
- Water Treatment Plant
- Restaurants & Commercial Kitchens

Top Features:

- Two Tanks One Valve System
- Down-flow & Up-flow Regeneration
- LED Multicolor Display
- Auto-Lock Feature
- Interval Backwash Times
- Manual Regeneration Function
- Automatic Parameter Storage



PT Watermart Perkasa
Email: sales@water.co.id Phone: +62-21-316-1671
Whatsapp (text only): +62815-8609-3500
Website: www.water.co.id