

## Runxin F77B1 (Model 53518)

### Overview

Runxin F77B1 is an automatic valve control specifically designed for large capacity softener and filter systems. It has a water treatment capacity of up to 18 m<sup>3</sup>/h, suitable for 24-30 inch diameter tank installations. Equipped with a digital control system, this valve can be configured as a softener or filter by simply modifying its internal connections. Designed for regeneration efficiency, high durability, and ease of installation both top-mounted and side-mounted.



### Specifications:

- Model 53518 (F77B1)
- Treatment Capacity 18 m<sup>3</sup>/h
- Inlet / Outlet 2" Male (2 "M)
- Drain 2" Male (2 "M)
- Base Valve 4"-8UN
- Riser Pipe 1.5" D-GB
- Tank Diameter 24" ~ 30"
- Water Pressure 0.15 MPa - 0.6 MPa
- Water Temperature 5°C - 50°C
- Turbidity Max. <20 FTU
- Environmental Temperature 5°C - 50°C
- Relative Humidity ≤95% (at 25°C)
- Adaptor Input Power: AC 100-240V 50/60Hz
- Output: DC 24V/1.5A

### Top Features:

- Corrosion Resistant Ceramic Seal
- Multi Function Automatic
- Smart Interlock Feature
- LED Dynamic Screen
- Changeable Parameters
- Remote Handling Input
- Multi-Level Frequency Rinsing
- Auto-Lock Button
- Power Off Indicator for More than 3 Days

### Material :

- Valve Head
- Seal
- Casing Panel
- Inlet/Outlet/Drain
- Connection
- Cable & Flow Meter

### Applications:

- Hotels & apartments
- Food and beverage factories
- Hospitals
- Boiler feed water
- Filtration System (if reconfigured into a filter): Large-scale domestic water treatment plants
- Agricultural irrigation systems



PT Watermart Perkasa  
Email: sales@water.co.id Phone: +62-21-316-1671  
Whatsapp (text only): +62815-8609-3500  
Website: www.water.co.id