



ION EXCHANGE RESIN

Dionix AS010 is a high-quality product used in water purification processes. It is effective in removing unwanted ions from water, thereby enhancing water quality and safety.

Physical and Chemical Features

Form	Spherical bead
Colour	White
Smell	A little smell
Melting temperature	
Density (g/ml)	1.04-1.10
Apparent density (g/ml)	
Solubility in water	0.65-0.73
Flashing point	
Ignition temperature	Insolubility
Water retention (%)	
Total Exchange Capacity (meq/g)	
Volume Exchange Capacity (meq/ml)	65-72
Bulk density (g/ml)	0.85 min
Special density (g/ml)	0.65-0.73
Particle size (%)	1.04-1.10
Effect size (mm)	(0.4 - 1.25 mm) ≥ 95
Homogeneous coefficient	0.50-0.90
Maximum swelling (%)	1.6 max
Ionic form supplied	40
	Cl

Application

Dionix AS010 offers improved resistance to heat and efficient SiO_2 treatment. It's effectively utilized in a variety of contexts, including demineralization, metal recovery, and the refinement of specific solutions such as sugar.

Additional Information

- Store in a cool and dry place
- Keep the container closed tightly to keep the resin from drying out and to stop dirt from getting in
- Wear protective gear for your eyes and skin when handling this product.
- For detailed safety information, please check the Safety Data Sheet or talk to our sales agent or the manufacturer
- Be careful not to contaminate the resin, as it is also used in food processing

