

AUTOTROL® 762 TIMER

METERED CONTROL WITH FULLY PROGRAMMABLE CYCLE TIMES AND SALT AMOUNT





FEATURES/BENEFITS

LCD display alternates between current flow rate and volume remaining

Large LCD display for simplified programming

Time of day super capacitor backup for power loss

Queued regeneration is indicated by a flashing icon

Easy installation with plug-in wiring harnesses

Easy electronic programming

Displays regeneration step and time remaining during regeneration

Programming stored in memory and will not be lost due to power outages

Adjustable Time of Regeneration

History

- Initial Setting Value
- Days since last regeneration
- Current Flow Rate
- Water used today since Time of Regeneration
- Water used since last regeneration
- Total water used since reset
- Average usage for each day of week
- Average service cycle
- Peak Flow Rate
- Day and Time of Peak Flow Rate
- Months since service
- Water used since last regeneration
- Number of regenerations since last serviced

OPTIONS

No salt detector indicates when to add salt *

Timer wall mount kits

Refill first for dry salt storage

* Not available on Magnum



UL recognized to the 979



Restriction of Hazardous Substance Compliant







FILTRATION & PROCESS

5730 NORTH GLEN PARK ROAD, MILWAUKEE, WI 53209

P: 262.238.4400 | F: 262.238.4404 | WWW.PENTAIRAQUA.COM | CUSTOMER CARE: 800.279.9404

4003063 REV B MR14 © 2014 Pentair Residential Filtration, LLC. All Rights Reserved.



PT Watermart Perkasa Email: sales@water.co.id Phone: +62-21-316-1671 Whatsapp (text only): +62815-8609-3500 Website: www.water.co.id