

AUTOTROL 361 VALVE

SEMI-AUTOMATIC FILTER VALVE

COMPACT, LOW-PROFILE SOLUTION FOR A BROAD RANGE OF FILTRATION APPLICATIONS



FEATURES/BENEFITS

Time-tested Duraflow flapper provides frictionless sealing for longer service life

Fiber-reinforced polymer valve body for superior strength and durability, non-corrosive, and UV-resistant

Low flow body with continuous service flow rate of 21 GPM with a backwash of 12 GPM

Full flow body with continuous service flow rate of 21 GPM with a backwash of 19 GPM

Environmental protective cover for water resistance, corrosion resistance, and UV stability

Designed for single tank systems only

No programming required- fixed cycle times

User-initiated regeneration knob

External drain line flow control

OPTIONS

Filter only control valve

Plumbing connections in .75"-1.25" NPT and BSP

Remote regeneration kit



PERFORMANCE

Motor Operating Voltage	12 VAC
-------------------------	--------

TRANSFORMER OPTIONS

North American Wall Mount	120/230 VAC
North American Outdoor	120 VAC
Japan Wall Mount	100 V
Australian Wall	240 V
British Wall	240
EU Cord Conn	240 V
European Wall Mount	240 VAC

VALVE SPECIFICATIONS

Valve Body	Glass-filled Noryl
Valve Color	Grey
Operating Pressure	20-125 PSI (1.38-8.61 BAR)
Water Temperature	35-100°F (2-38°C)
Ambient Temperature	35-122°F (2-50°C)
Cycle Steps	Service, backwash, fast rinse
Service Capabilities	Removable cam, flapper access
Cam Position Indicator	Knob

PERFORMANCE

Drain Line Flow Control	4-20 gpm
Low Flow Body	Service: 21 gpm Backwash: 12 gpm Fast Rinse: 5 gpm
Full Flow Body	Service: 21 gpm Backwash: 19 gpm Fast Rinse: 5 gpm

VALVE CONNECTIONS

Tank Thread	2.5"
Inlet/Outlet	1" NPT or 1" BSP
Inlet/Outlet (center to center)	4"
Drain Location	0.75" below inlet/outlet

DIMENSIONS

Width	8.6"
Height	3.35"
Riser Tube Dia.	1.05"
Riser Height	Flush +/- 0.5"

FIXED CYCLE STEP TIMES

Backwash, 60Hz	18 min
Backwash, 50Hz	21 min
Fast Rinse, 60Hz	6 min
Fast Rinse, 50Hz	7 min



13845 BISHOPS DR., SUITE 200, BROOKFIELD, WI 53005 USA
P: 262.238.4400 | WATERPURIFICATION.PENTAIR.COM | CUSTOMER CARE: 800.279.9404 | tech-support@pentair.com
© 2018 Pentair Residential Filtration, LLC. All rights reserved.

§For a detailed list of where Pentair trademarks are registered, please visit waterpurification.pentair.com/brands. Pentair trademarks and logos are owned by Pentair plc or its affiliates. Third party registered and unregistered trademarks and logos are the property of their respective owners.

43649 REV C JL18



PT Watermart Perkasa
Email: sales@water.co.id Phone: +62-21-316-1671
Whatsapp (text only): +62815-8609-3500
Website: www.water.co.id