

## FLECK 4650 HOT WATER CONTROL VALVE

**MADE IN THE  
USA**  
OF FOREIGN & DOMESTIC PARTS



### FEATURES/BENEFITS

Lead-free brass valve body for superior strength and durability

Continuous service flow rate of 20 GPM with a backwash of 7 GPM

Backwash capability accommodates softener tanks up to 12" and filters up to 10" in diameter

Fully adjustable 3- or 5-cycle control for efficient and reliable water treatment system

Time-tested, hydraulically-balanced piston for service and regeneration

Designed with double backwash for reduced hardness leakage

Rugged-built electromechanical timer designed with heavy duty 3/8" wide plastic gears

### OPTIONS

Softener control valves

Brine cam auxiliary switch

Plumbing connections in 3/4" or 1", NPT and sweat

Fiber-reinforced polymer or stainless steel bypass valve

Hot water

Electromechanical 12-day clock regeneration

**Electromechanical Timer-** Simple to adjust and easy to service with quick access to all internal components



## VALVE SPECIFICATIONS

Valve Material	Lead-free brass*
Inlet/Outlet	3/4" or 1" NPT/Sweat
Cycles	7

## FLOW RATES (50 PSI INLET) – VALVE ALONE

Continuous 15 psi drop	20 GPM (4.5 m <sup>3</sup> /h)
Peak 25 psi drop	26 GPM (5.9 m <sup>3</sup> /h)
Cv flow at 1 psi drop	5.2
Max. Backwash 25 psi drop	7 GPM (1.6 m <sup>3</sup> /h)

## REGENERATION

Downflow/Upflow	Downflow only
Adjustable Cycles	Brine fill only
Time Available Electromechanical	180 min/regeneration continuous moving piston

## DIMENSIONS

Distributor Pilot	1.05" O.D. (26.7 mm)
Drain Line	1/2" NPTF
Brine Valve 1600:	3/8"
Injector System	1600
Mounting Base	2.5"– 8 NPSM
Height from Top of Tank	7" (178 mm)
Riser Tube Diameter	3/4" (19 mm)
Riser Height	Flush with top of tank

## TYPICAL APPLICATIONS

Water Softener	6 - 12" diameter
Filters	6 - 10" diameter based on 10 GPM/ft <sup>2</sup>

## ADDITIONAL INFORMATION

Electrical Rating	24/110V 50/60 Hz
Max. VA	3
Estimated Shipping Weight Time Clock:	7 lbs
Pressure Hydrostatic:	300 psi (20 bar)
Working:	20 - 125 psi (1.4 - 8.5 bar)
Temperature Hot Water Valve:	34 - 180° F (1 - 82° C)
Softener, Filter, Time Clock, 1600 Brine System	

\*As defined in the U.S. EPA Safe Drinking Water Act; the product also meets California Proposition 65 Standards for lead-free brass.



13845 BISHOPS DR., SUITE 200, BROOKFIELD, WI 53005 USA  
P: 262.238.4400 | WATERPURIFICATION.PENTAIR.COM | CUSTOMER CARE: 800.279.9404 | tech-support@pentair.com  
© 2018 Pentair Residential Filtration, LLC. All rights reserved.  
§For a detailed list of where Pentair trademarks are registered, please visit [waterpurification.pentair.com/brands](http://waterpurification.pentair.com/brands)  
Pentair plc or its affiliates. Third party registered and unregistered trademarks and logos are the property of their  
40744 REV F JL18



PT Watermart Perkasa  
Email: [sales@water.co.id](mailto:sales@water.co.id) Phone: +62-21-316-1671  
Whatsapp (text only): +62815-8609-3500  
Website: [www.water.co.id](http://www.water.co.id)